

GD-2004S


Eco Solvent Printer (with four I3200-E1 print heads)



Grando Eco Solvent Ink



Four I3200-E1 Heads



* 2m Four I3200-E1 Print Heads Speed

360x2400dpi - 4pass	100 m ² /h
720x1800dpi - 6pass	67 m ² /h
720x2400dpi - 8pass	47 m ² /h

Air suction intelligent dust removal system


The air suction system and intelligent dust removal, which can eliminate the ink fog generated in the printing process, restore the authenticity of the prints, prolong the print head service life, and increase the durability of the machine to the greatest extent.

AI Voice dialogue

Grando GD2004s has AI voice recognition functions: printer on/off control, light status control, and fan status control. In addition, our GD2004 also has a low-ink alarm function and a waste ink removal alarm.

Remote control system

Sitting at home or in the office, we can remotely control our devices through a mobile phone. (Switch on the printer with just one click through the remote control menu.)



Suitable for PP, photo paper, car sticker, lightbox film, canvas, non-woven fabric, etc

• Technical Specifications

Model	GD-2004S	
Print Head	Four I3200-E1 Print Heads	
Printing Technology	Piezoelectric Inkjet	
Acceptable Media	Width	2030 (mm)
	Thickness	Maximum 39.3 mil(1 mm)
Weight	220.5 lb.(100 kg)	
	Printing Width 2000 (mm)	
Ink Cartridges	Type	Eco Solvent Ink
	Capacity	220ml secondary ink cartridge with 3L ink tank
Color	4 colors (Cyan, Magenta, Yellow, Black)	
	Printing Resolution	Maximum 2400 dpi
Printing Speed	4pass(360x2400dpi) :	100 sqm/h
	6pass(720x1800dpi) :	67 sqm/h
	8pass(720x2400dpi) :	47 sqm/h
Media Heating System	Intergrated post heater & Infrared Dryer & Fan system	
Interface	Ethernet Interface	
Power	8000W	
Power Supply	AC 220V ± 10%, 50/60 HZ	
Dimensions(with stand)	112.6(W)x31.7(D)x60(H) in.	
	(2861(W)x806(D)x1533(H) mm)	
Weight(with stand)	1058.2 lb. (480 kg)	
Package Dimensions	106(W)x31(D)x30.7(H) in.	
	(2700(W)x790(D)x780(H) mm)	
Package Weight	Entirety Packing : 1278.7 lb. (580 kg) Split Packing : 1036.2 lb. (470 kg)	
Environment	Power on	Temperature: 59 ℉ to 90 ℉ [15 C to 32 C] / Humidity: 35 to 80% (no condensation)
	Power off	Temperature: 41 ℉ to 104 ℉ [5 C to 40 C] / Humidity: 20 to 80% (no condensation)
Accessories	Stand, take-up and discharge device, cold air drying system, large ink supply system, etc.	




Suction wind system intelligent dust removal



4H I3200 Moisturizing System




Built in temperature and humidity display



High quality DC servo motor has good stability and long service life



THK high-precision mute rail



Three-foot pinch roller structure brings more stable feeding accuracy



Infrared heater and cooling fan



External power supply, intelligent rolling system.